



# Nedo® Product Information



## Laser receiver ACCEPTOR XL green

**ACCEPTOR XL green** is the new laser receiver with XL detector field and digital mm display for green line lasers.

The new **ACCEPTOR XL green** laser receiver extends the range of a green line laser to up to 120 m. The deviation of the laser level from the zero line of the **ACCEPTOR XL green** is shown digitally in mm on the two large displays on the front and rear. Perfect for quickly determining height differences.

**ACCEPTOR XL green** is compatible with the Nedo multi-line lasers X-Liner 360.2 green, X-Liner 3D green, X-Liner 4D green and X-Liner 6 green.

### Features:

- Digital laser receiver for green Nedo line lasers
- mm display
- Extremely robust design
- Large detector field: 60mm
- Large LC display on front and back
- Display illumination
- Adjustable volume
- Switchable LEDs
- Strong magnets for fixing to steel girders
- Protected against powerful jet water to IP 67
- 3 adjustable accuracy levels
- Automatic switch-off
- Incl. robust receiver holder
- Suitable for green line lasers with 510-540nm and 5kHz pulse frequency



### Nedo ACCEPTOR XL green

Ref.-No.	430 322
Length of detector field	60mm
Working range	up to 120 m Ø
Protection class	IP 67
Operating temperature	-10°C to +50°C
Operation duration	up to 45 h
Power supply	1 x 1.5 V Typ AA

Technical data subject to change



Precise surveying and measuring

### Nedo GmbH & Co. KG

Hochgerichtstrasse 39-43  
D-72280 Dornstetten  
Phone +49 (0)7 443 24 01-0  
info@nedo.com  
www.nedo.com